

# ONTEC APN 31P M D2R W TM-AN.31P.DR03W



No: 1525



No: 88-116197



No: 1525




No: 1525



No: V1.4



|                                            |                                   |
|--------------------------------------------|-----------------------------------|
| Producer                                   | <b>TM Technologie</b>             |
| Category                                   | <b>emergency luminaires</b>       |
| Application                                | <b>evacuation route direction</b> |
| Family                                     | <b>ONTEC AP</b>                   |
| Colour/Colour - RAL                        | <b>white , RAL9003</b>            |
| Colour structure                           | <b>smooth, gloss</b>              |
| Version                                    | <b>DATA2 RADIO</b>                |
| Operating mode                             | <b>M</b>                          |
| Duration time                              | <b>3 h</b>                        |
| Protection degree                          | <b>IP20</b>                       |
| Impact protection degree                   | <b>IK06</b>                       |
| Appliance classes                          | <b>II</b>                         |
| Material                                   | <b>plastic</b>                    |
| Installation method*                       | <b>ceiling, surface</b>           |
| Adapted to use a pictogram                 | <b>yes</b>                        |
| Pictogram included                         | <b>yes</b>                        |
| Evacuation sign dimensions                 | <b>311x158 mm</b>                 |
| Pictogram type                             | <b>foil</b>                       |
| Graphic number                             | <b>K3</b>                         |
| Luminous flux                              | <b>&gt;200 cd/m²</b>              |
| Visibility                                 | <b>32 m</b>                       |
| Colour temperature                         | <b>5700</b>                       |
| Nominal voltage AC                         | <b>210-250 V</b>                  |
| Light source                               | <b>LED</b>                        |
| Maximum light power                        | <b>2.5 W</b>                      |
| LED lifetime                               | <b>50000 h</b>                    |
| Minimum temperature                        | <b>+10 °C</b>                     |
| Maximum temperature                        | <b>+40 °C</b>                     |
| Battery                                    | <b>LiFePO4/C 6.4V 1.5Ah</b>       |
| Warranty (body, electronics, light source) | <b>60 months</b>                  |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>403 mm x 61 mm x 211 mm</b>    |



\* Some of mounting methods are possible only with additonal accessory dedicated for that product.