

PRIMO AP 30D CB B

TM-AP.30D.CB01B



No: 1725



No: 4329/2021
Valid until:
19.05.2026



No: B_BK_60112_0427_2024
Valid until:
24.01.2030



No: 1725



No: DC-UAE-0180
Valid until:
19.05.2026



No: 1725



No: V1.0



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO AP
Colour/Colour - RAL	black , RAL9005
Colour structure	painted
Version	CB - central battery
Operating mode	CB
Protection degree	IP20
Impact protection degree	IK07
Appliance classes	I
Material	steel
Installation method*	ceiling
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	300x150 mm
Evacuation sign dimensions	300x150 mm
Pictogram type	sticker
Graphic number	K3
Luminous flux	>500 cd/m²
Visibility	30 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	2 W
LED lifetime	50000 h
Minimum temperature	-15 °C
Maximum temperature	+55 °C

Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	323 mm x 61 mm x 228 mm

