

# PRIMO AP 30D CB W TM-AP.30D.CB01W



No: 1725



No: 4329/2021  
Valid until:  
19.05.2026



No: B\_BK\_60112\_0427\_2024  
Valid until:  
24.01.2030



No: 1725



No: DC-UAE-0180  
Valid until:  
19.05.2026



No: 1725



No: V1.0



|                            |                                   |
|----------------------------|-----------------------------------|
| Producer                   | <b>TM Technologie</b>             |
| Category                   | <b>emergency luminaires</b>       |
| Application                | <b>evacuation route direction</b> |
| Family                     | <b>PRIMO AP</b>                   |
| Colour/Colour - RAL        | <b>white , RAL9003</b>            |
| Colour structure           | <b>painted</b>                    |
| Version                    | <b>CB - central battery</b>       |
| Operating mode             | <b>CB</b>                         |
| Protection degree          | <b>IP20</b>                       |
| Impact protection degree   | <b>IK07</b>                       |
| Appliance classes          | <b>I</b>                          |
| Material                   | <b>steel</b>                      |
| Installation method*       | <b>ceiling</b>                    |
| Adapted to use a pictogram | <b>yes</b>                        |
| Pictogram included         | <b>yes</b>                        |
| Pictogram dimensions       | <b>300x150 mm</b>                 |
| Evacuation sign dimensions | <b>300x150 mm</b>                 |
| Pictogram type             | <b>sticker</b>                    |
| Graphic number             | <b>K3</b>                         |
| Luminous flux              | <b>&gt;500 cd/m<sup>2</sup></b>   |
| Visibility                 | <b>30 m</b>                       |
| Colour temperature         | <b>5700 K</b>                     |
| Nominal voltage AC         | <b>210-250 V</b>                  |
| Nominal voltage DC         | <b>186-254 V</b>                  |
| Light source               | <b>LED</b>                        |
| Maximum light power        | <b>2 W</b>                        |
| LED lifetime               | <b>50000 h</b>                    |
| Minimum temperature        | <b>-15 °C</b>                     |
| Maximum temperature        | <b>+55 °C</b>                     |

|                                            |                                |
|--------------------------------------------|--------------------------------|
| Warranty (body, electronics, light source) | <b>60 months</b>               |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>323 mm x 61 mm x 228 mm</b> |

