

# INDUST B2L CB DALI2 A

## TM-B2.0LCD0090A



No: 3625



No: 5386/2024  
Valid until:  
15.05.2029



No: 3625



No: 2016




No: 3625



No: V1.0



|                                            |                                             |
|--------------------------------------------|---------------------------------------------|
| Producer                                   | TM Technologie                              |
| Category                                   | emergency luminaires                        |
| Application                                | evacuation route direction, tunnel lighting |
| Family                                     | INDUST B2                                   |
| Version                                    | CD - CB DALI2                               |
| Operating mode                             | CB                                          |
| Protection degree                          | IP66, IP69                                  |
| Impact protection degree                   | IK08                                        |
| Appliance classes                          | I                                           |
| Material                                   | stainless steel                             |
| Colour structure                           | raw                                         |
| Installation method*                       | surface, wall                               |
| Adapted to use a pictogram                 | yes                                         |
| Luminous flux                              | >200 cd/m <sup>2</sup>                      |
| Luminous flux emergency                    | 1000 lm                                     |
| Nominal voltage AC                         | 220-240 V                                   |
| Nominal voltage DC                         | 186-254 V                                   |
| Light source                               | LED                                         |
| Maximum light power                        | 5 W                                         |
| LED lifetime                               | 50000 h                                     |
| Colour temperature                         | 5700 K                                      |
| Minimum temperature                        | -25 °C                                      |
| Maximum temperature                        | +45 °C                                      |
| Battery                                    | -                                           |
| DALI type                                  | A                                           |
| Warranty (body, electronics, light source) | 60 months                                   |
| Net dimensions L x W x H [±2 mm]           | 481 mm x 75 mm x 692 mm                     |



\* Some of mounting methods are possible only with additional accessory dedicated for that product.