

INDUST B5D CB DALI 2 H

TM-B5.D0CD0090H



No: 3725



No: 5436/2024
Valid until:
09.07.2029



No: 3725



No: 2016



No: 3725



No: V1.0



Producer **TM Technologie**
Category **emergency luminaires**
Application **evacuation route direction, tunnel lighting**

Family **INDUST B5**

Colour structure **raw**

Version **CD - CB DALI2**

Operating mode **CB**

Protection degree **IP66, IP69**

Impact protection degree **IK08**

Appliance classes **I**

Material **stainless steel**

Installation method* **surface, wall**

Adapted to use a pictogram **yes**

Pictogram dimensions **357x672 mm**

Evacuation sign dimensions **330x660 mm**

Pictogram type **plexiglass PMMA**

Luminous flux **>200 cd/m²**

Visibility **66 m**

Colour temperature **5700 K**

Nominal voltage AC **220-240 V**

Nominal voltage DC **186-254 V**

Light source **LED**

Maximum light power **1.5 W**

LED lifetime **50000 h**

Minimum temperature **-25 °C**

Maximum temperature **+45 °C**

Battery **-**

DALI type **A**

Warranty (body, electronics, light source) **60 months**

Net dimensions **L x W x H [±2 mm]** **560 mm x 105 mm x 795 mm**

