

INDUST B 5DF CBM H TM-B5.DLCBM09LH



No: 3725



No: 5436/2024
Valid until:
09.07.2029



No: 3725



No: 3725



No: DIT_004



No: V1.0



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction, tunnel lighting
Family	INDUST B5
Colour structure	raw
Version	CBM - Central addressable modulation battery
Operating mode	CB
Protection degree	IP66, IP69
Impact protection degree	IK08
Appliance classes	I
Material	stainless steel
Installation method*	surface, wall
Adapted to use a pictogram	yes
Pictogram dimensions	357x672 mm
Evacuation sign dimensions	330x660 mm
Pictogram type	plexiglass PMMA
Luminous flux	>200 cd/m ²
Visibility	66 m
Colour temperature	5700 K
Nominal voltage AC	220-240 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	1.6 W
LED lifetime	50000 h
Minimum temperature	-25 °C
Maximum temperature	+45 °C
Battery	-
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	560 mm x 105 mm x 795 mm



* Some of mounting methods are possible only with additonal accessory dedicated for that product.