

BOA IN RC1 60 NM ST TM-BIRC1STN6000



No: 1125



No: 5912/2025
Valid until:
29.11.2030




No: B_BK_60112_0421_2024
Valid until:
24.01.2030



No: 1125



No: 1125





No: DIT_001



No: V2.1



Producer	TM Technologie
Application	escape route lighting
Family	BOA IN
Version	standard
Operating mode	NM
Duration time	1 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Installation method*	ceiling, flush-mounted, surface
Luminous flux emergency	293 lm
Light source	LED
Maximum light power	2.5 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	24 months
Net dimensions H x Ø [±2 mm]	21 mm x 50 mm



h	a	b	c	d
2,5	7,5	17	-	-
3	9	20	-	-
4	11	25	-	-
5	12,5	29	-	-
6	13	32	-	-
7	5	28	-	-
8	3	25	-	-
9	4	20	-	-
10	4	18	-	-

Emin ≥ 1 lx

* Some of mounting methods are possible only with additonal accessory dedicated for that product.