

TM-CB L2-48/34 SEL ANTHRACITE

TM-C4.09634SELD



No: 4325



No: 4325



No: 4325



The **TM-CB 48 V** Central Battery System is a modern and energy-efficient solution for powering emergency lighting from a single, central point. Thanks to its compact and modular design, the system can be easily expanded and connected to luminaires with a total power of up to 1440 W, depending on the model selected. An intuitive, easy-to-read display facilitates operation and quick access to information about the status of the installation. The low voltage of 48 V ensures a high level of safety during installation and servicing. Depending on the version, the system offers monitoring of circuits or individual luminaires, ensuring constant supervision and reliability in everyday operation.

Producer	TM Technologie
Application	central battery
Colour/Colour - RAL	anthracite , RAL7016
Appliance classes	I
Protection degree	IP30
Warranty (body, electronics)	60 months
Net dimensions L x W x H [±2 mm]	420 mm x 238 mm x 836 mm

POSSIBILITIES

Maximum number of emergency fittings in the system	160 pcs.
Maximum number of emergency fittings circuit and channel	20 pcs.
Maximum distance between control panel and luminaire	1000 m
C-Panel (display)	yes
Allowed topology	parallel connection
Maximum luminaires power CB 1h	960 W
Maximum luminaires power CB 2h	587 W
Maximum luminaires power CB 3h	407 W
Maximum luminaires power CB 8h	187 W

TELECOMMUNICATION CABLES

POWER CABLES

<i>Power cables with appropriate fire classification and circuit integrity in case of fire (if applicable)</i>	
AC power cable cross section	3 x 1.5 - 4.0 mm ²
Type and cross section of luminaires power cable	2 x 1,5 - 2,5 mm ²

TOPOLOGY

AKU AGM 12V 34Ah TM-A5L034.UN.B1



BATTERIES | power supply for luminaires included in the system

Battery made in VRLA (AGM) technology, compatible with TM-CB model:

- » TM-CB M 7/33-112-07
- » TM-CB L2-48/34 SEL

Producer's datasheet:

