

SUB-DISTRIBUTION TM-CB M SUB PR20 ANTHRACITE TM-CM.2000020DA



No: 33A23



No: 5251/2024
Valid until:
20.12.2028



No: 33A23



No: 33A23



No: 063-UWB-0591
Valid until:
20.12.2028



No: CBM-01/24



Producer	TM Technologie
Application	central battery
Colour/Colour - RAL	anthracite , RAL7016
Appliance classes	I
Protection degree	IP30
Warranty (body, electronics)	60 months
Net dimensions L x W x H [±2 mm]	480 mm x 196 mm x 582 mm

POSSIBILITIES

Maximum number of emergency fittings in the system	400 pcs.
Maximum number of emergency fittings circuit and channel	20 pcs.
Maximum number of circuits substation and subdistribution	20 pcs.
Maximum distance between control panel and luminaire	300 m
I/O module using possibility	yes
Allowed topology	parallel connection, star connection

Sub-distribution TM-CB M PR20

The sub-distribution board enables the system to be extended by another 20 circuits.

- » number of circuits: 20
- » maximum number of luminaires on one circle: 20
- » colour: anthracite

TELECOMMUNICATION CABLES

Telecommunication cables with appropriate fire classification and circuit integrity in case of fire (if applicable)

Maximum length of communication cable	1000 m
Maximum resistance	75 Ω
Maximum conductor capacitance	140 nF/km

POWER CABLES

Power cables with appropriate fire classification and circuit integrity in case of fire (if applicable)

AC power cable cross section	3 x 2,5 - 6,0 mm ²
Type and cross section of luminaires power cable	3 x 0,5 - 4,0 mm ²
Communication protocol	RS485, PLC

TOPOLOGY

