

ITECH C1 CB W

TM-IT.C1CB0060W



No: 0925



No: 4570/2022
Valid until:
10.04.2027



No: 88-137959
Valid until:
20.03.2029



No:
B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0925



No: 0925





No: V2.12






Producer	TM Technologie
Application	escape route lighting
Family	ITECH
Colour/Colour - RAL	white , RAL9003
Version	CB - central battery
Operating mode	CB
Protection degree	IP65
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, ceiling, at an angle
Luminous flux emergency	369 lm
Light source	LED
Maximum light power	2 W
Active power	4.59 W
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	-25 °C
Maximum temperature	+55 °C

Warranty (body, electronics, light source) **60 months**

Net dimensions **H x Ø [±2 mm]** **74 mm x 171 mm**



				
2,5	9	20	-	-
3	10	23	-	-
4	12,5	28	-	-
5	13	32	-	-
6	10	34	-	-
7	6,5	32	-	-
8	5,5	30	-	-
9	5	25	-	-
10	6	20	-	-

E_{min} ≥ 1 lx

* Some of mounting methods are possible only with additional accessory dedicated for that product.