

ITECH C2 305 M DALI2 W TM-IT.C2DLM360W



No: 0925



No: 4570/2022
Valid until:
10.04.2027



No: B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0925



No: 7492



No: 0925



No: DIT_001



No: V2.12



DiiA Certificate

<https://www.dali-alliance.org/products/7492/itech>

Producer **TM Technologie**

Category **emergency luminaires**

Application **escape route lighting**

Family **ITECH**

Colour/Colour - RAL **white , RAL9003**

Version **DALI2**

Operating mode **M**

Duration time **3 h**

Protection degree **IP65**

Impact protection degree **IK06**

Appliance classes **II**

Material **plastic**

Colour structure **smooth, gloss**

Installation method* **surface, flush-mounted, suspended, ceiling, at an angle**

Luminous flux emergency **478 lm**

Nominal voltage AC **210-250 V**

Nominal voltage DC **- V**

Light source **LED**

Maximum light power **4.5 W**

LED lifetime **50000 h**

Colour temperature **5700 K**

Minimum temperature **+ 0 °C**



Maximum temperature **+40 °C**

Battery **LiFePO4/C (LN) 6.4V 3.0-3.2Ah**

DALI type **A**

Warranty (body, electronics, light source) **60 months**

Net dimensions **H x Ø [±2 mm]** **74 mm x 171 mm**



* Some of mounting methods are possible only with additional accessory dedicated for that product.