

ONTEC C C1 302 M AT W

TM-OC.C1ATM300W



No: 0125



No: 4397/2021
Valid until:
11.09.2026



No: 88-128463
Valid until:
25.05.2026



No:
B_BK_60112_0424_2024
Valid until:
24.01.2030



No: 0125



No: 2291559.02-
UAE
Valid until:
05.11.2026



No: 0125




No: DIT_001




No: V1.14



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC C
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Installation method*	flush-mounted, ceiling
Luminous flux emergency	260 lm
Light source	LED
Maximum light power	3 W
Active power	7 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C 6.4V 1.5Ah
Warranty (body, electronics, light source)	36 months
Net dimensions H x Ø [±2 mm]	14 mm x 90 mm





2,5	9	20	-	-
3	10	23	-	-
4	11	27,5	-	-
5	9,5	30	-	-
6	6	30	-	-
7	3,5	25	-	-
8	3,5	20	-	-
9	-	-	-	-
10	-	-	-	-

$E_{min} \geq 1 \text{ lx}$