

ONTEC C C1H 303 M D2R W TM-OC.CHDRM300W



No: 0125



No: 4397/2021
Valid until:
11.09.2026



No: 88-128463
Valid until:
25.05.2026



No:
B_BK_60112_0424_2024
Valid until:
24.01.2030



No: 0125



No: 2291559.02-
UAE
Valid until:
05.11.2026





No: 0125



No: V1.14



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC C
Colour/Colour - RAL	white , RAL9003
Version	DATA2 RADIO
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Installation method*	flush-mounted, ceiling
Luminous flux emergency	353 lm
Light source	LED
Maximum light power	3 W
Active power	8.6 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 6.4V 3.0-3.2Ah
Warranty (body, electronics, light source)	60 months
Net dimensions H x Ø [±2 mm]	14 mm x 90 mm



	a	b	c	d
2,5	9,5	21	-	-
3	10,5	24	-	-
4	12,5	29,5	-	-
5	13,5	34	-	-
6	11,5	36	-	-
7	6,5	34	-	-
8	4,5	30	-	-
9	4	25	-	-
10	4	20	-	-

Emin ≥ 1 lx

* Some of mounting methods are possible only with additional accessory dedicated for that product.