

ONTEC E E1P 01 CB K TM-OE.EPCB0000K



No: 0225



No: 4408/2021
Valid until:
09.10.2026



No:
B_BK_60112_0425_2024
Valid until:
24.01.2030




No: 0225



No: 0225



No: V1.12



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	ONTEC E
Colour/Colour - RAL	green , RAL6018
Colour structure	matte , satin, smooth
Version	CB1 - central battery
Operating mode	CB
Protection degree	IP20
Impact protection degree	IK05
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, wall
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	265x139 mm
Evacuation sign dimensions	250x125 mm
Pictogram type	foil
Graphic number	K3
Luminous flux	>300 cd/m²
Visibility	25 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	1 W
LED lifetime	50000 h
Minimum temperature	-15 °C
Maximum temperature	+55 °C

Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	277 mm x 33 mm x 153 mm

