

# ONTEC E E1P 301 M DALI W TM-OE.EPDAM300W



No: 0225



No: 4408/2021  
Valid until:  
09.10.2026



No:  
B\_BK\_60112\_0425\_2024  
Valid until:  
24.01.2030



No: 0225



No: 3333



No: 0225



No: DIT\_001




No: V1.12



DiiA Certificate

<https://www.dali-alliance.org/products/3333/vip-r>

|                                            |                                     |
|--------------------------------------------|-------------------------------------|
| Producer                                   | <b>TM Technologie</b>               |
| Category                                   | <b>emergency luminaires</b>         |
| Application                                | <b>evacuation route direction</b>   |
| Family                                     | <b>ONTEC E</b>                      |
| Colour/Colour - RAL                        | <b>white , RAL9003</b>              |
| Colour structure                           | <b>matte , satin, smooth</b>        |
| Version                                    | <b>DALI</b>                         |
| Operating mode                             | <b>M</b>                            |
| Duration time                              | <b>3 h</b>                          |
| Protection degree                          | <b>IP20</b>                         |
| Impact protection degree                   | <b>IK05</b>                         |
| Appliance classes                          | <b>II</b>                           |
| Material                                   | <b>plastic</b>                      |
| Installation method*                       | <b>surface, flush-mounted, wall</b> |
| Adapted to use a pictogram                 | <b>yes</b>                          |
| Pictogram included                         | <b>yes</b>                          |
| Pictogram dimensions                       | <b>265x139 mm</b>                   |
| Evacuation sign dimensions                 | <b>250x125 mm</b>                   |
| Pictogram type                             | <b>foil</b>                         |
| Graphic number                             | <b>K3</b>                           |
| Luminous flux                              | <b>&gt;300 cd/m<sup>2</sup></b>     |
| Visibility                                 | <b>25 m</b>                         |
| Colour temperature                         | <b>5700 K</b>                       |
| Nominal voltage AC                         | <b>210-250 V</b>                    |
| Light source                               | <b>LED</b>                          |
| Maximum light power                        | <b>1 W</b>                          |
| LED lifetime                               | <b>50000 h</b>                      |
| Minimum temperature                        | <b>+10 °C</b>                       |
| Maximum temperature                        | <b>+35 °C</b>                       |
| Battery                                    | <b>LiFePO4/C 6.4V 1.5Ah</b>         |
| DALI type                                  | <b>A</b>                            |
| Warranty (body, electronics, light source) | <b>60 months</b>                    |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>277 mm x 33 mm x 153 mm</b>      |



\* Some of mounting methods are possible only with additional accessory dedicated for that product.