

ONTEC R C1 60 NM AT L TM-OR.C1ATN600L



No: 0425



No: 4410/2021
Valid until:
04.09.2026



No: 88-128814



No:
B_BK_60112_0424_2024
Valid until:
24.01.2030



No: 0425



No: 2291559.02-
UAE
Valid until:
05.11.2026




No: 0425




No: DIT_001





No: V3.0



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC R
Colour/Colour - RAL	yellow , RAL1016
Version	autotest
Operating mode	NM
Duration time	1 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, wall, ceiling, at an angle
Luminous flux emergency	306 lm
Light source	LED
Maximum light power	2 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	130 mm x 31 mm x 130 mm





2,5	9	20	-	-
3	10,5	23	-	-
4	12,5	28	-	-
5	13,5	32	-	-
6	12	33	-	-
7	6	31	-	-
8	4	25	-	-
9	4,5	20	-	-
10	2,5	7	-	-

$E_{min} \geq 1 \text{ lx}$