

# PRIMO P M2 180 NM AT W TM-P0.M2.AT04W



No: 1725



No: 4329/2021  
Valid until:  
19.05.2026



No:  
B\_BK\_60112\_0427\_2024  
Valid until:  
24.01.2030




No: 1725



No: DC-UAE-  
0180  
Valid until:  
19.05.2026



No: 1725





No: DIT\_001



No: V1.2



|                                            |                                      |
|--------------------------------------------|--------------------------------------|
| Producer                                   | <b>TM Technologie</b>                |
| Application                                | <b>anti-panic lighting</b>           |
| Family                                     | <b>PRIMO P</b>                       |
| Colour/Colour - RAL                        | <b>white , RAL9003</b>               |
| Version                                    | <b>autotest</b>                      |
| Operating mode                             | <b>NM</b>                            |
| Duration time                              | <b>3 h</b>                           |
| Protection degree                          | <b>IP20</b>                          |
| Impact protection degree                   | <b>IK03</b>                          |
| Appliance classes                          | <b>I</b>                             |
| Material                                   | <b>steel</b>                         |
| Installation method*                       | <b>flush-mounted, ceiling</b>        |
| Luminous flux emergency                    | <b>651 lm</b>                        |
| Light source                               | <b>LED</b>                           |
| Maximum light power                        | <b>5.1 W</b>                         |
| Active power                               | <b>3.6 W</b>                         |
| Nominal voltage AC                         | <b>210-250 V</b>                     |
| LED lifetime                               | <b>50000 h</b>                       |
| Colour temperature                         | <b>5700 K</b>                        |
| Minimum temperature                        | <b>+5 °C</b>                         |
| Maximum temperature                        | <b>+40 °C</b>                        |
| Battery                                    | <b>LiFePO4/C (LN) 6.4V 4.5-4.8Ah</b> |
| Warranty (body, electronics, light source) | <b>36 months</b>                     |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>357 mm x 90 mm x 88 mm</b>        |



\* Some of mounting methods are possible only with additional accessory dedicated for that product.