

PRIMO D C1 60 NM D2 B

TM-PD.C1BDN600B



No: 0525



No: 4672/2022
Valid until:
13.06.2027



No: 88-128507



No:
B_BK_60112_0428_2024
Valid until:
24.01.2030



No: 0525



No: DC-UAE-
0214
Valid until:
13.06.2027



No: 0525




No: DIT_001







No: V1.5



Producer	TM Technologie
Application	escape route lighting
Family	PRIMO D
Colour/Colour - RAL	black , RAL9005
Version	DATA2
Operating mode	NM
Duration time	1 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	I
Material	steel
Installation method*	flush-mounted, ceiling
Luminous flux	- cd/m²
Luminous flux emergency	279 lm
Light source	LED
Maximum light power	3 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	90 mm x 90 mm x 13 mm





					
2,5		9	20	-	-
3		10	23	-	-
4		11,5	28	-	-
5		9,5	31	-	-
6		5	30	-	-
7		4	28	-	-
8		4	21	-	-
9		3	16	-	-
10		3,5	13	-	-

$E_{min} \geq 1 \text{ lx}$