

PRIMO D M2 302 M D2 B

TM-PD.M2BDM300B



No: 0525



No: 4672/2022
Valid until:
13.06.2027



No: 88-128507



No:
B_BK_60112_0428_2024
Valid until:
24.01.2030



No: 0525



No: DC-UAE-
0214
Valid until:
13.06.2027



No: 0525




No: DIT_001








No: V1.5



Producer	TM Technologie
Application	anti-panic lighting
Family	PRIMO D
Colour/Colour - RAL	black , RAL9005
Version	DATA2
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	I
Material	steel
Installation method*	flush-mounted, ceiling
Luminous flux	- cd/m²
Luminous flux emergency	224 lm
Light source	LED
Maximum light power	3 W
Active power	7 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C 6.4V 1.5Ah
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	90 mm x 90 mm x 13 mm





					
2,5		3,5	7,5	3,5	7,5
3		3,5	8,5	3,5	8,5
4		4	10,5	4	10,5
5		5	12	5	12
6		5	14	5	14
7		5	15	5	15
8		4,5	16	4,5	16
9		3	17	3	17
10		4	16	4	16

$E_{min} \geq 0,5 \text{ lx}$