

PRIMO E 40E 01 CB B

TM-PE.4ECB0000B



No: 0625



No: 4599/2022
Valid until:
20.03.2027



No: 88-141849
Valid until:
28.02.2027



No:
B_BK_60112_0429_2024
Valid until:
24.01.2030



No: 0625



No: DC-UAE-
0204
Valid until:
20.03.2027



No: 0625



No: V1.9



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO E
Colour/Colour - RAL	black , RAL9005
Colour structure	painted
Version	CB - central battery
Operating mode	CB
Protection degree	IP20
Impact protection degree	IK05
Appliance classes	I
Material	steel
Installation method*	surface, flush-mounted, wall
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	417x229 mm
Evacuation sign dimensions	400x200 mm
Pictogram type	foil
Graphic number	K3
Luminous flux	>200 cd/m²
Visibility	40 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
Maximum light power	2.7 W
LED lifetime	50000 h
Minimum temperature	-15 °C
Maximum temperature	+55 °C

Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	422 mm x 39 mm x 234 mm

