

PRIMO E 80E 180 M AT M TM-PE.8EATM800M



No: 0625



No: 4599/2022
Valid until:
20.03.2027



No: 88-128526



No:
B_BK_60112_0429_2024
Valid until:
24.01.2030




No: 0625



No: DC-UAE-0204
Valid until:
20.03.2027



No: 0625



No: DIT_001



No: V1.9



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO E
Colour structure	gloss
Version	autotest
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK05
Appliance classes	I
Material	stainless steel
Installation method*	surface, flush-mounted, wall
Adapted to use a pictogram	yes
Pictogram dimensions	817x429 mm
Evacuation sign dimensions	800x400 mm
Pictogram type	foil
Luminous flux	>150 cd/m²
Visibility	80 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Light source	LED
Maximum light power	3 W
LED lifetime	50000 h
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C 3.2V 3.0Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	822 mm x 39 mm x 434 mm

