

ONTEC PPN 31P M D2R W TM-PN.31P.DR03W



No: 1525



No: 88-116197



No: 1525



No: 1525



No: DIT_001



No: V1.4



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	ONTEC PP
Colour/Colour - RAL	white , RAL9003
Colour structure	smooth, gloss
Version	DATA2 RADIO
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	ceiling, flush-mounted
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	311x158 mm
Evacuation sign dimensions	311x158 mm
Pictogram type	foil
Graphic number	K3
Luminous flux	>200 cd/m²
Visibility	32 m
Colour temperature	5700
Nominal voltage AC	210-250 V
Light source	LED
Maximum light power	2.5 W
LED lifetime	50000 h
Minimum temperature	+10 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C 6.4V 1.5Ah
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	403 mm x 108 mm x 211 mm

