

PRIMO PP 40D 180 M D2 M

TM-PP.40D.BD03M



No: 1725



No: 4329/2021
Valid until:
19.05.2026



No:
B_BK_60112_0427_2024
Valid until:
24.01.2030




No: 1725



No: DC-UAE-
0180
Valid until:
19.05.2026



No: 1725



No: DIT_001



No: V1.0



Producer **TM Technologie**
Category **emergency luminaires**
Application **evacuation route direction**
Family **PRIMO PP**

Colour structure **gloss**
Version **DATA2**
Operating mode **M**
Duration time **3 h**
Protection degree **IP20**
Impact protection degree **IK07**
Appliance classes **I**
Material **stainless steel**
Installation method* **ceiling**
Adapted to use a pictogram **yes**
Pictogram included **yes**
Pictogram dimensions **400x200 mm**
Evacuation sign dimensions **400x200 mm**
Pictogram type **sticker**
Graphic number **K3**
Luminous flux **>500 cd/m²**
Visibility **40 m**
Colour temperature **5700 K**
Nominal voltage AC **210-250 V**
Light source **LED**
Maximum light power **2 W**
LED lifetime **50000 h**
Minimum temperature **+5 °C**
Maximum temperature **+40 °C**
Battery **LiFePO4/C 6.4V 1.5Ah**
Warranty (body, electronics, light source) **60 months**
Net dimensions **L x W x H [±2 mm]** **423 mm x 91 mm x 279 mm**

