

# PRIMO Q 30E 180 M D2R W TM-PQ.3EDRM800W



No: 2925



No: 2925



No: 2925



No: DIT\_001



No: V2.3



|                                            |                                      |
|--------------------------------------------|--------------------------------------|
| Producer                                   | <b>TM Technologie</b>                |
| Application                                | <b>evacuation route direction</b>    |
| Family                                     | <b>PRIMO Q</b>                       |
| Colour/Colour - RAL                        | <b>white , RAL9003</b>               |
| Version                                    | <b>DATA2 RADIO</b>                   |
| Operating mode                             | <b>M</b>                             |
| Duration time                              | <b>3 h</b>                           |
| Protection degree                          | <b>IP20</b>                          |
| Impact protection degree                   | <b>IK05</b>                          |
| Appliance classes                          | <b>I</b>                             |
| Material                                   | <b>steel</b>                         |
| Installation method*                       | <b>surface, suspended, ceiling</b>   |
| Luminous flux                              | <b>&gt;150 cd/m<sup>2</sup></b>      |
| Light source                               | <b>LED</b>                           |
| Maximum light power                        | <b>2.1 W</b>                         |
| Active power                               | <b>3.01 W</b>                        |
| Nominal voltage AC                         | <b>210-250 V</b>                     |
| LED lifetime                               | <b>50000 h</b>                       |
| Colour temperature                         | <b>5700 K</b>                        |
| Minimum temperature                        | <b>+5 °C</b>                         |
| Maximum temperature                        | <b>+40 °C</b>                        |
| Battery                                    | <b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b> |
| Warranty (body, electronics, light source) | <b>60 months</b>                     |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>399 mm x 399 mm x 192 mm</b>      |

