

PRIMO PPZ 30D 180 M D2 B TM-PZ.30D.BD03B



No: 1725



No: 4329/2021
Valid until:
19.05.2026



No: B_BK_60112_0427_2024
Valid until:
24.01.2030



No: 1725



No: DC-UAE-0180
Valid until:
19.05.2026



No: 1725



No: DIT_001



No: V1.1



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO APZ
Colour/Colour - RAL	black , RAL9005
Colour structure	painted
Version	DATA2
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK07
Appliance classes	I
Material	steel
Installation method*	ceiling
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	319x193 mm
Evacuation sign dimensions	300x150 mm
Pictogram type	foil
Graphic number	K3, D3
Luminous flux	>500 cd/m²
Visibility	30 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Light source	LED
Maximum light power	1.8 W
LED lifetime	50000 h
Minimum temperature	+5 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C 6.4V 1.5Ah
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	324 mm x 61 mm x 783 mm

