

ONTEC S20 M2 180 M AT W IP65 TM-S2.M2ATM360W



No: 1625



No: 4302/2021
Valid until:
15.04.2026



No: 88-129369



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No:
2291559.02.UAE
Valid until:
05.11.2026



No: 1625



No: DIT_004





No: V3.0



Producer **TM Technologie**
Application **anti-panic lighting, evacuation route direction**

Family **ONTEC S20**
Colour/Colour - RAL **white , RAL9003**
Version **autotest**
Operating mode **M**
Duration time **3 h**
Protection degree **IP65**
Impact protection degree **IK08**
Appliance classes **II**
Material **plastic**
Installation method* **surface, flush-mounted, suspended, wall, ceiling, at an angle**
Luminous flux **>2 cd/m²**
Luminous flux emergency **309 lm**
Light source **LED**
Maximum light power **2.5 W**
Active power **4.7 W**
Nominal voltage AC **210-250 V**
LED lifetime **50000 h**
Colour temperature **5700 K**
Minimum temperature **+ 0 °C**
Maximum temperature **+40 °C**
Battery **LiFePO4/C (LN) 2x3.2V 1.5-1.6Ah**
Warranty (body, electronics, light source) **36 months**
Net dimensions **L x W x H [±2 mm]** **227 mm x 40 mm x 120 mm**





2,5	3,5	8	3,5	8
3	3,5	9	3,5	9
4	4,5	11	4,5	11
5	5	12,5	5	12,5
6	5	14,5	5	14,5
7	5	16	5	16
8	5,5	17	5,5	17
9	5,5	18	5,5	18
10	5	19	5	19

$E_{min} \geq 0,5 \text{ lx}$