

ONTEC S20 M2X CBM W IP65 TM-S2.MXCBM060W



No: 1625



No: 4302/2021
Valid until:
15.04.2026



No: 88-144520
Valid until:
28.02.2027



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No:
2291559.01.UAE
Valid until:
28.10.2026



No: 1625



No: DIT_004



No: V3.0



Producer **TM Technologie**
Application **anti-panic lighting, evacuation route direction**

Family **ONTEC S20**
Colour/Colour - RAL **white , RAL9003**
Version **CBM - Central addressable modulation battery**

Operating mode **CB**

Protection degree **IP65**

Impact protection degree **IK08**

Appliance classes **II**

Material **plastic**

Installation method* **surface, flush-mounted, suspended, wall, ceiling, at an angle**

Luminous flux **>2 cd/m²**

Luminous flux emergency **154(L);309(H) lm**

Light source **LED**

Maximum light power **2.5 W**

Active power **4.4 W**

Nominal voltage AC **210-250 V**

Nominal voltage DC **186-254 V**

LED lifetime **50000 h**

Colour temperature **5700 K**


Minimum temperature **-15 °C**


Maximum temperature **+55 °C**

Battery **-**

Warranty (body, electronics, light source) **60 months**

Net dimensions **L x W x H [±2 mm]** **227 mm x 40 mm x 120 mm**





2,5	3,5	8	3,5	8
3	3,5	9	3,5	9
4	4,5	11	4,5	11
5	5	12,5	5	12,5
6	5	14,5	5	14,5
7	5	16	5	16
8	5,5	17	5,5	17
9	5,5	18	5,5	18
10	5	19	5	19

$E_{min} \geq 0,5 \text{ lx}$