

# ONTEC S30 C2 CB W IP65

## TM-S3.C2CB0060W



No: 1625



No: 4302/2021  
Valid until:  
15.04.2026



No: 88-146912  
Valid until:  
24.09.2029



No:  
B\_BK\_60112\_0426\_2024  
Valid until:  
24.01.2030



No: 1625



No: 2291560.01-  
UAE  
Valid until:  
08.10.2026



No: 1625




No: V3.0



|                          |                                                                      |
|--------------------------|----------------------------------------------------------------------|
| Producer                 | <b>TM Technologie</b>                                                |
| Application              | <b>escape route lighting</b>                                         |
| Family                   | <b>ONTEC S30</b>                                                     |
| Colour/Colour - RAL      | <b>white , RAL9003</b>                                               |
| Version                  | <b>CB - central battery</b>                                          |
| Operating mode           | <b>CB</b>                                                            |
| Protection degree        | <b>IP65</b>                                                          |
| Impact protection degree | <b>IK08</b>                                                          |
| Appliance classes        | <b>II</b>                                                            |
| Material                 | <b>plastic</b>                                                       |
| Installation method*     | <b>surface, flush-mounted, suspended, wall, ceiling, at an angle</b> |
| Luminous flux emergency  | <b>533 lm</b>                                                        |
| Light source             | <b>LED</b>                                                           |
| Maximum light power      | <b>5.1 W</b>                                                         |
| Active power             | <b>6.9 W</b>                                                         |
| Nominal voltage AC       | <b>210-250 V</b>                                                     |
| Nominal voltage DC       | <b>186-254 V</b>                                                     |
| LED lifetime             | <b>50000 h</b>                                                       |
| Colour temperature       | <b>5700 K</b>                                                        |
| Minimum temperature      | <b>-25 °C</b>                                                        |
| Maximum temperature      | <b>+55 °C</b>                                                        |

|                                            |                                |
|--------------------------------------------|--------------------------------|
| Warranty (body, electronics, light source) | <b>60 months</b>               |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>327 mm x 40 mm x 170 mm</b> |



\* Some of mounting methods are possible only with additional accessory dedicated for that product.