

ONTEC S30 C5 CB W IP65

TM-S3.C5CB0060W



No: 1625



No: 4302/2021
Valid until:
15.04.2026



No: 88-146912
Valid until:
24.09.2029



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No: 2291560.01-
UAE
Valid until:
08.10.2026



No: 1625




No: V3.0



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC S30
Colour/Colour - RAL	white , RAL9003
Version	CB - central battery
Operating mode	CB
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	1145 lm
Light source	LED
Maximum light power	5.8 W
Active power	11.3 W
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	-25 °C
Maximum temperature	+35 °C

Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	327 mm x 40 mm x 170 mm





8	19,5	47	-	-
9	20	51	-	-
10	18,5	54	-	-
11	17	55	-	-
12	15	57	-	-
13	12,5	56	-	-
14	11	55	-	-
15	9	53	-	-
16	7	50	-	-
17	5	45	-	-
18	4,5	40	-	-
19	4	35	-	-
20	3,5	30	-	-

$E_{min} \geq 1 \text{ lx}$