

PRIMO TRL M1 180 NM AT W + ADAPTER TM-TL.M1ATN80SW



No: 3225



No: 3225



No: 3225



No: DIT_001



No: V1.3



Producer **TM Technologie**

Family **PRIMO TRL**

Colour/Colour - RAL **white , RAL9003**

Version **autotest**

Operating mode **NM**

Duration time **3 h**

Protection degree **IP20**

Impact protection degree **IK08**

Appliance classes **I**

Material **steel**

Installation method* **ceiling, surface**

Luminous flux emergency **326 lm**

Light source **LED**

Maximum light power **2.5 W**

Active power **1.6 W**

Nominal voltage AC **210-250 V**

Nominal voltage DC **- V**

LED lifetime **50000 h**

Colour temperature **5700 K**







Minimum temperature **+ 0 °C**

Maximum temperature **+ 35 °C**

Battery **LiFePO4/C 3.2V 3.0Ah**

Warranty (body, electronics, light source) **36 months**

Net dimensions **L x W x H [±2 mm]** **350 mm x 50 mm x 89 mm**



2,5	3,5	9	3,5	9
3	4,5	10	4,5	10
4	5	12,5	5	12,5
5	5,5	14,5	5,5	14,5
6	5	16,5	5	16,5
7	4,5	18	4,5	18
8	4,5	19	4,5	19
9	4	20	4	20
10	4	20	4	20

E_{min} ≥ 0,5 lx

* Some of mounting methods are possible only with additional accessory dedicated for that product.