

# PRIMO TRL M1 180 NM DALI W TM-TL.M1DAN800W



No: 3225



No: 3225



No: 1955



No: 3225



No: DIT\_001



No: V1.3



DiiA Certificate

<https://www.dali-alliance.org/products/1955/vip-rs>

Producer

**TM Technologie**

Category

**emergency luminaires**

Family

**PRIMO TRL**

Colour/Colour - RAL

**white , RAL9003**

Version

**DALI**

Operating mode

**NM**

Duration time

**3 h**

Protection degree

**IP20**

Impact protection degree

**IK08**

Appliance classes

**I**

Material

**steel**

Colour structure

**painted**

Installation method\*

**ceiling, surface**

Luminous flux emergency

**326 lm**

Nominal voltage AC

**210-250 V**

Nominal voltage DC

**- V**

Light source

**LED**

Maximum light power

**2.5 W**

LED lifetime

**50000 h**

Colour temperature

**5700 K**

Minimum temperature

**+ 0 °C**

Maximum temperature

**+ 35 °C**

Battery

**LiFePO4/C 6.4V 1.5Ah**

DALI type




**D**

Warranty (body, electronics, light source)

**60 months**

Net dimensions **L x W x H** [±2 mm]

**350 mm x 50 mm x 89 mm**



|     |     |      |     |      |
|-----|-----|------|-----|------|
| 2,5 | 3,5 | 9    | 3,5 | 9    |
| 3   | 4,5 | 10   | 4,5 | 10   |
| 4   | 5   | 12,5 | 5   | 12,5 |
| 5   | 5,5 | 14,5 | 5,5 | 14,5 |
| 6   | 5   | 16,5 | 5   | 16,5 |
| 7   | 4,5 | 18   | 4,5 | 18   |
| 8   | 4,5 | 19   | 4,5 | 19   |
| 9   | 4   | 20   | 4   | 20   |
| 10  | 4   | 20   | 4   | 20   |

\* Some of mounting methods are possible only with additional accessory dedicated for that product.