

PRIMO TRL M1 180 NM DALI W + ADAPTER TM-TL.M1DAN80SW



No: 3225



No: 3225



No: 1955



No: 3225



No: DIT_001



No: V1.3



DiiA Certificate

<https://www.dali-alliance.org/products/1955/vip-rs>

Producer

TM Technologie

Category

emergency luminaires

Family

PRIMO TRL

Colour/Colour - RAL

white , RAL9003

Version

DALI

Operating mode

NM

Duration time

3 h

Protection degree

IP20

Impact protection degree

IK08

Appliance classes

I

Material

steel

Colour structure

painted

Installation method*

ceiling, surface

Luminous flux emergency

326 lm

Nominal voltage AC

210-250 V

Nominal voltage DC

- V

Light source

LED

Maximum light power

2.5 W

LED lifetime

50000 h

Colour temperature

5700 K

Minimum temperature

+ 0 °C

Maximum temperature

+ 35 °C

Battery

LiFePO4/C 6.4V 1.5Ah

DALI type



D

Warranty (body, electronics, light source)

60 months

Net dimensions **L x W x H** [±2 mm]

350 mm x 50 mm x 89 mm



2,5	3,5	9	3,5	9
3	4,5	10	4,5	10
4	5	12,5	5	12,5
5	5,5	14,5	5,5	14,5
6	5	16,5	5	16,5
7	4,5	18	4,5	18
8	4,5	19	4,5	19
9	4	20	4	20
10	4	20	4	20

* Some of mounting methods are possible only with additional accessory dedicated for that product.